

Murphy

Concrete Products Ltd.



Contact Us

Our sales, customer support and technical team are available to speak with you at any stage.



Sales Contact

willie@murphyconcrete.ie



Office

Tel: 00-353-53-9236348
info@murphyconcrete.ie
Old Dublin Road, Kilcannon,
Enniscorthy, Co. Wexford,
Ireland. Y21 AF43

www.murphyconcreteproducts.ie

TOP FILL TROUGHS



Features and specifications:

- Drinking Troughs are designed with Animal Safety in mind, with internal and external rounded corners.
- Concrete Drinking Troughs are robust and will not lose their shape. They will also withstand any movement by livestock.
- All Troughs are reinforced using polymer fibre and reinforced steel to achieve maximum tensile strength.
- It is recommended that in extreme low temperatures to fully drain the Drinking Trough to prevent damage.
- Easy draining of water can be achieved by removing the tapered solid rubber bung.
- The rubber bung size for the 150-to-500-gallon Trough is 64mm outlet and the 30-to-70-gallon Trough is 44mm outlet.
- The valve protection concrete cover is fully removable for ease of access.
- All valves are mounted onto a steel galvanised bracket. This bracket is bolted to the top rim of the trough.
- All troughs are manufactured to 40N certified EN 206 concrete.

Trough Size

30 gallons
70 gallons
150 gallons
300 gallons
400 gallons
500 gallons

Dimensions

1450mm long, 650mm wide, 330mm depth
2110mm long, 650mm wide, 500mm depth
1920mm long, 1020mm wide, 610mm depth
2580mm long, 1220mm wide, 740mm depth
3330mm long, 1200mm wide, 750mm depth
4140mm long, 1200mm wide, 750mm depth

